

## PACKAGE SPEC:

```
PACKAGE swkmadv IS
  TYPE swkmadv_rec IS
  RECORD (student_id      spriden.spriden_id%TYPE,
          student_name    varchar2(30),
          degc_code       sgbstdn.sgbstdn_degc_code_1%TYPE,
          maj_desc        stvmajr.stvmajr_desc%TYPE,
          conc_desc       stvmajr.stvmajr_desc%TYPE,
          advisor_id      spriden.spriden_id%TYPE,
          advisor_name    varchar2(30));

  -- for the DML - a table of records
  TYPE swkmadv_table
  IS TABLE OF swkmadv_rec
  INDEX BY PLS_INTEGER;

  PROCEDURE swkmadv_query(p_majadv_qry IN OUT swkmadv_table,
                          run_term IN varchar2,
                          run_dept IN varchar2);

END;
```

## PACKAGE BODY:

```
PACKAGE BODY swkmadv IS
  PROCEDURE swkmadv_query(p_majadv_qry IN OUT swkmadv_table,
                          run_term IN varchar2,
                          run_dept IN varchar2)
  IS
    ii NUMBER;

  CURSOR swkmadv_select IS
    select b.spriden_id,
           b.spriden_last_name || ', ' || b.spriden_first_name,
           a.sgbstdn_degc_code_1,
           c.stvmajr_desc,
           d.stvmajr_desc,
           e.spriden_id,
           (case when e.spriden_last_name is not null then
              (rtrim(e.spriden_last_name) || ', ' || rtrim(e.spriden_first_name)) end)
    from sgbstdn a, spriden b, stvmajr c, stvmajr d, sgradvr, spriden e
    where a.sgbstdn_dept_code = run_dept
```

```
and a.sgbstdn_term_code_eff = (select max(f.sgbstdn_term_code_eff)
                               from sgbstdn f
                               where f.sgbstdn_pidm = a.sgbstdn_pidm
                               and f.sgbstdn_term_code_eff <= run_term)
and a.sgbstdn_lvl_code = 'UG'
and a.sgbstdn_majr_code_1 = c.stvmajr_code
and a.sgbstdn_majr_code_conc_1 = d.stvmajr_code(+)
and b.spriden_pidm = a.sgbstdn_pidm
and b.spriden_change_ind is null
and sgradvr_pidm(+) = a.sgbstdn_pidm
and sgradvr_term_code_eff (+) = run_term
and sgradvr_advr_code(+) = 'MAJR'
and e.spriden_pidm(+) = sgradvr_advr_pidm
and e.spriden_change_ind is null;
```

**BEGIN**

```
OPEN swkmadv_select;
```

```
ii:=1;
```

```
LOOP
```

```
FETCH swkmadv_select
```

```
INTO
```

```
p_majadv_qry(ii).student_id,
```

```
p_majadv_qry(ii).student_name,
```

```
p_majadv_qry(ii).degc_code,
```

```
p_majadv_qry(ii).maj_desc,
```

```
p_majadv_qry(ii).conc_desc,
```

```
p_majadv_qry(ii).advisor_id,
```

```
p_majadv_qry(ii).advisor_name;
```

```
EXIT when swkmadv_select%NOTFOUND;
```

```
ii := ii + 1;
```

```
END LOOP;
```

```
END;
```

```
END;
```